



ALL-AMERICAN HOSE™
 217 Titusville Rd.
 Union City, PA 16438

TM Hose (Military)

All American Hose is a world class distributor of Lay Flat Hose

Hose Construction – 100% high tenacity yarn, extruded with thru the weave polyurethane construction. Liner and Cover minimum 3000 psi tensile strength.

Chemical Resistance – Hose capable of withstanding exposure to most hydro-carbons, gasoline, oils, alkalis and grease with no effect on the performance of the hose.

Ozone Resistance – The hose shows no visible signs of cracking of the liner or cover when subjected to testing in accordance with ASTM D1149-64, 100 PPHM/122°F/70 hours.

Abrasion Resistance – Abrasion resistance shall be 5X that of conventional rubber hose, 300,000 cycles on a Taber abrasion tester without exposure of the jacket.

Temperature Range - - 60°F (-51°C) to 180°F(82°C)

Designed for maximum service life and low operating cost.

Fast deployment and retrieval – saving time and money

Easy Handling for deployment and retrieval – Installed on reels or custom packaging

Standard length – 660' (200M), shorter lengths available

Color – Desert Tan

Optional Encapsulated antistatic discharge wire

Manufactured within our ISO-9001 certified quality assurance system

Performance Chart

Product	Inside Diameter (in)	Wall Thickness (in)	Average Weight (lbs. /ft.)	Working Pressure (psi)	Burst (psi)
TM20	2"	.100	.387	300	900
TM30	3"	.130	.580	250	750
TM40	4"	.130	.825	200	600
TM60	6"	.130	1.375	225	675

3/16