



ALL-AMERICAN HOSE™

217 Titusville Rd.
Union City, PA 16438

Agricultural Products – Sludge Hose

All-American Hose is a world class distributor of Lay Flat Hose

Hose Construction – 100% high tenacity yarn, extruded with thru the weave polyurethane construction. Liner and Cover minimum 3,000 psi tensile strength.

Chemical Resistance – Hose must be capable of withstanding exposure to most hydro-carbons, gasoline, oils, alkalis and grease with no effect on the performance of the hose.

Ozone Resistance – The hose shall show no visible signs of cracking of the liner or cover when subjected to testing in accordance with ASTM D1149-64, 100 PPHM/122°F/70 hours

Abrasion Resistance – Abrasion resistance shall be 5X that of conventional rubber hose, 300,000 cycles on a Taber abrasion tester without exposure of the jacket.

Designed for maximum service life and low operating cost.

Fast deployment and retrieval – saving time and money

Easy to store and transport

Standard length – 660' (200M), shorter lengths available

Color – Brown, Blaze Orange

Manufactured within our ISO-9001 certified quality assurance system

Performance Chart

Product	Inside Diameter	Wall Thickness	Weight Lbs./Ft	Burst Pressure, PSI	Tensile Strength, Lbs.
TSX45	4.5'	.200	1.34	600	30,744
TSX50	5"	.200	1.42	500	35,100
TSX55	5.5"	.200	1.50	500	44,000
TSX60	6"	.220	1.90	900	42,500
TSX70	7"	.210	2.15	750	52,398
TSX72	7.25"	.210	2.20	750	52,398

9/19