



**HARD
SUCTION**



USA MADE

TANK-FLEX

CONVENTIONAL HARD RUBBER WIRE REINFORCED SUCTION HOSE

For rural fire departments that require pick-up-and-go portability, Tank-Flex is the everyday essential. A durable hard suction hose, it features a tough synthetic Ethylene Propylene Diene Monomer (EPDM) rubber cover that resists wear on the fireground while standing up to ozone damages. A special wire helix and nylon fabric reinforced liner boosts hose durability, so it can withstand pressure if required. Tank-Flex is more flexible than most standard hard suction hoses, allowing for better all-around handling with quick and easy hookup. It is engineered for drafting from any rural water source; and is also approved for municipal water supply transfer.



FEATURES:

- Wire reinforced liner and smooth ozone-resistant cover. Can withstand pressure, if required.
- Easy to transport and more flexible than traditional hard suction hoses for fast hookup.
- Constructed with soft cuff ends for greater coupling retention.
- Designed for full vacuum. Suitable for hard suction applications, drafting from rural water sources and approved for municipal water supply transfer.
- Assembled in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system.
- Five year warranty.

HOSE SIZING AND SPECIFICATIONS

SIZE	WORKING PRESSURE	BURST	WEIGHT (FOR 10' UNCOUPLED)	BOWL SIZE
IN	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
2½"	150 (1035)	450 (3100)	16 (7.3)	3"
3"	150 (1035)	450 (3100)	20 (9.1)	3¾"
4"	150 (1035)	450 (3100)	28 (12.7)	4⅝"
4½"	165 (1135)	495 (3410)	39 (17.7)	5⅜"
5"	165 (1135)	495 (3410)	43 (19.5)	5⅞"
6"	165 (1135)	495 (3410)	58 (26.3)	6⅞"



ALL-AMERICAN HOSE™

all-americanhose.com | 814-438-7616 | 217 Titusville Road, Union City, PA 16438 USA