



**ATTACK**

# DURA-PAK

## NYLON DOUBLE JACKET ATTACK HOSE

When introduced, Dura-Pak started an industry-wide trend toward lightweight high-rise hose. Originally designed for back-pack use, Dura-Pak folds tightly for small spaces, hose beds and high-rise packs. Because it is so durable, many departments have selected Dura-Pak for frontline attack duties.



**HIGH-RISE**




**NATIONAL FIRE HOSE**

Polyurethane Liner

Nylon Inner Jacket

Nylon Outer Jacket



### FEATURES:

- Both jackets made from 100% high strength, low stretch, air-entangled nylon 6.6 along with a lining of thermoplastic polyurethane for reduced weight while remaining kink resistant.
- Reverse twill weave of the inner jacket provides a smoother waterway and superior liner system, surpassed only by Ponn Conquest™.
- Standard Dura-Cote™ protective treatment (see page 27 for more information).
- Suitable for CAFS and foam concentrate applications.
- Highly resistant to ozone and oxidation.
- Can be used for potable water in an emergency. The polyurethane lining material meets NSF/ANSI Standard 61 for drinking water.
- Manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO-9001 certified quality assurance system.



**CAFS**



**POTABLE WATER**



**USA MADE**

### COUPLINGS

Aluminum NH/NST or IPT Threaded

### COLORS



### CONSTRUCTION

Nylon Double Jacket  
Polyurethane Inner Liner

### TEMPERATURE RANGE

-40°F to 150°F (-40°C to 65°C)

### HOSE SIZING AND SPECIFICATIONS

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (FOR 50' COUPLED)	FLAT WIDTH	BOWL SIZE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	IN
1 1/2"	400 (2760)	800 (5515)	1200 (8275)	20 (9.1)	2.80"	1 15/16"
1 3/4"	400 (2760)	800 (5515)	1200 (8275)	22 (10)	3.20"	2 1/8"
2 1/2"	400 (2760)	800 (5515)	1200 (8275)	30 (13.6)	4.50"	2 15/16"
3"	400 (2760)	800 (5515)	1200 (8275)	38 (17.2)	5.30"	3 3/16"

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

### HOW TO ORDER

TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
DP	15 = 1 1/2" 17 = 1 3/4" 25 = 2 1/2" 30 = 3"	X	50 = 50' 100 = 100'	Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White (coated)	15 = 1 1/2" 20 = 2" 25 = 2 1/2" 30 = 3"	N = NH I = IPT	Aluminum

**Part No. Example: DP17X50O15N** = DP Dura-Pak Hose, 1 3/4" ID by 50' Length, Orange, 1 1/2" NH/NST Aluminum Coupling